

AC-630 Diaphragm Meter for Propane



Features:

- Convuluted Diaphragms
- Unique valve design
- Smaller meter profile
- Superior corrosion resistance
- Regular or TC tangent
- Automatic meter reader compatibility
- Permanently lubed bearings
- Temperature compensation available from -30°F to 140°F
- 10 (std.) or 25 (opt.) PSIG MAOP
- Full warranty
- 20 LT, 30 LT, 45 LT and #3-4 Sprague Hubs with 1 1/4" NPTM Swivels
- Pointer or odometer index
- Conforms to ANSI B109.2-1992: Diaphragm-Type Gas Displacement Meters (500-Cubic-Feet-per-hour Capacity and over)

Dimensions:

| | |
|--------------------------|--------|
| Weight | 21 lbs |
| Connection to Connection | 8 1/4" |
| Height | 15.0" |
| Width | 10.6" |
| Depth | 10.0" |

Capacities:

| Rated Gas Capacity for 1.53 S.G. Propane | | | |
|--|--------------------------|----------------------|--------------|
| Inlet Pressure PSIG | Inches W.C. Differential | Capacity CFH Propane | Capacity BTU |
| .25 | 1/2" | 395 | 1,000,900 |
| .25 | 2" | 827 | 2,097,124 |
| 1 | 2" | 839 | 2,128,899 |
| 2 | 2" | 870 | 2,208,336 |
| 5 | 2" | 949 | 2,406,927 |
| 10 | 2" | 1071 | 2,716,730 |
| 15 | 2" | 1184 | 3,002,701 |
| 20 | 2" | 1259 | 3,193,349 |
| 25 | 2" | 2160 | 3,431,659 |

1 – based on Propane- 2537 BTU/CfF

Options:

- Pulse Output (1 pulse/CuFt)
- Remote totalizer (battery powered/wall mount)
- Wireless transmitter (see photo below)
- Internet Reading Options

