




Knowledge to Shape Your Future

Diaphragm Meter Product Line – Propane Vapor (1.53 s.g.)

	Model	Temperature Compensation	Maximum Allowable Operating Pressure	Available Hub Sizes	Center-to-Center Distance	Capacity* (Propane Gas)	Shipping Weight
	METRIS 250	TC & NTC	5 PSIG 10 PSIG(Optional)	10LT, #1 Sprague, 1- 1/4", 20LT, 30LT	6"	158 CFH @ .5"w.c.diff 252 CFH @ 1"w.c.diff	9#
	METRIS RM (regulator & meter)	TC & NTC	5 PSIG 10 PSIG(Optional)	Inlet 3/4" or 1" Back Outlet 10LT, #1 Sprague, 1- 1/4", 20LT, 30LT	NA	158 CFH @ .5"w.c.diff 252 CFH @ 1"w.c.diff	15#
	400A	TC & NTC	10 PSIG 25 PSIG(Optional)	20LT, 30LT, 45LT, #4 Sprague	6 25/32" or 8 1/4"	252 CFH @ .5"w.c.diff	14#
Standard Top 	675A*	TC & NTC	25 PSIG	30LT, 45LT, #4 Sprague	10"	498 CFH @ .5"w.c.diff 1055 CFH @ 2"w.c.diff	41#
	800A*	TC & NTC	25 PSIG	30LT, 45LT, 60LT, 100LT, #5 Sprague	11"	561 CFH @ .5"w.c.diff 1216 CFH @ 2"w.c.diff	41#
	1000A*	TC & NTC	25 PSIG	45LT, 60LT, 100LT, #5 Sprague	11"	655 CFH @ .5"w.c.diff 1395 CFH @ 2"w.c.diff	41#
ET Top 							

* Models 675A, 800A, and 1000A are available in Standard Top or ET Top,

*Note: 2537 BTU/ SCF of Propane (1.53 s.g.)

FOLLIN FLO CONTROLS
a division of **BIG WAVE inc**

Itron Inc. represented by:
Follin Flo-Controls
www.FollinFlo-Controls.com

Phone: (617) 290-2134
Fax: (240) 250-8907
E-mail: sales@FollinFlo-Controls.com