



**NEPTUNE®**

Neptune Technology Group Inc.

# TRICON/E3® Transmitter

*TRICON/E3 transmitters provide an interface between the water meter and an electronic controller for batching processes, monitoring flow totalization, and/or flow rate data.*



An electronic digital pulse output with the 4–20mA option is available for customers requiring both digital and analog outputs. Reverse flow indication is available with the high frequency forward/reverse pulse output option.

The TRICON/E3 transmitter mounts between the meter maincase and the register. The bayonet-type mount allows the TRICON/E3 to be easily retrofitted to many existing Neptune meters without interruption. Contact Neptune regarding compatibility.

The TRICON/E3 with the 4–20mA option provides an analog signal that is proportional to the flow. Together, the digital pulse signal and the 4–20mA output provide information on total consumption and flow rate for close monitoring of water usage.

The TRICON/E3 with the high frequency forward/reverse pulse output option can be used in applications where directional flow monitoring is required in addition to total consumption and flow information.

Every Neptune meter meets or exceeds the latest AWWA standards ensuring accurate, dependable performance.

Neptune TRICON/E3 units are ideally suited for monitoring/controlling total flow rate data such as:

- Instantaneous readout of customer consumption via remote instrumentation or computer
- Batch or continuous process
- Water softening regeneration
- Demineralization
- Reverse osmosis
- Chemical treatment/injection
- Filtration
- Boiler feed water make-up
- Cooling tower water make-up
- Irrigation
- High or low rate alarming
- Reverse flow alarming

Dual optical switches allow the TRICON/E3 to distinguish between forward and reverse rotation, eliminating false pulse generation under low or no flow conditions.

## Warranty

Neptune provides a limited warranty with respect to its TRICON/E3 transmitters for performance, materials, and workmanship.

## Key Features

- Electronic pulse output proportional to the meter's rate of flow
- Electronic pulse output available with 4–20mA output or high frequency forward/reverse pulse output
- Mounts between the meter and register – Direct Read, ARB®, or ProRead AutoDetect
- Utilizes dual optical switch type design which is more accurate and reliable than the older single optical switch designs
- Stainless steel ball bearings minimize torque
- Tamperproof seal pin to prevent unauthorized access
- In-line adaptability allows installation or service without interrupting the meter service

## Performance Data

Meter Type & Size	Pulses/ US Gallons	Flow Rate @ 4 mA Output (US GPM)	Flow Rate Value @ 20 mA Output (US GPM)
<b>T-10</b>			
5/8"	578.1	0	20
3/4"	322.6	0	30
1"	150.8	0	50
1 1/2"	67.57	0	100
2"	37.3	0	160
<b>Tru/Flo Compound (Turbine Side) and HP Tru/Flo (Turbine Side)</b>			
2" HP	6.095	0	200
3"	2.890	0	450
4"	1.590	0	1,000
6"	0.464	0	2,000
<b>HP Turbine</b>			
1 1/2"	6.095	0	160
2"	6.095	0	200
3"	11.20	0	450
4"	7.556	0	1,200
6"	0.7273	0	3,000
8"	0.7556	0	4,000
10"	0.7556	0	6,500
12"	0.7556	0	8,000
16"	0.07556	0	13,500
20"	0.07556	0	22,000
<b>HP Protectus III</b>			
4"	7.556	0	1,200
6"	0.7556	0	2,888
8"	0.6095	0	4,959
10"	0.5333	0	9,209

## Electrical Characteristics (over 0-70°C operating temperature)

Parameter	Description	Min	Max	Units
<b>HF and UP/DN Digital Pulse Model</b>				
V <sub>cc</sub>	Supply Voltage (DC)	11.5	26.5	Volts
I <sub>s</sub>	Supply Current	0.020	0.050	Amps
V <sub>ol</sub>	Low Output Voltage	0	0.4	Volts
V <sub>oh</sub>	High Output Voltage	8.5	12	Volts
I <sub>ol</sub>	Current at V <sub>ol</sub>		.010	Amps
I <sub>oh</sub>	Current at V <sub>oh</sub>		.010	Amps
t <sub>r</sub> l-h	Output Rise Time		2*	µsec
t <sub>f</sub> h-l	Output Fall Time		2*	µsec
Measured with R <sub>L</sub> = 2.4 Kohms, C <sub>L</sub> = 50 pF				
<b>4-20 ma Model</b>				
V <sub>cc</sub>	Supply Voltage (DC)	22.5	26.5	Volts
I <sub>s</sub>	Supply Current		0.1	Amps
R <sub>L</sub>	Loop Resistance	0	600	Ohms
Gain	Scaling Accuracy		0.5	%FS
Zero	Offset Accuracy		0.2	%FS
Note: initial calibration is 1% total				
<b>Both Models (unless otherwise specified)</b>				
	Operating Temperature	0	70	Degrees C
	Storage Temperature	-40	85	Degrees C
	Supply Voltage	-30	30	Volts
	Output Load (Pulse Output)	1200		Ohms
	Output Current (Pulse Output)		0.01	Amps

## Specifications

- Sizes:
  - T-10 (5/8"-2")
  - HP Turbine (1 1/2"-20")
  - Tru/Flo Compound (2"-6"x8")
  - HP Fire Service Turbine (3"-10")
  - HP Protectus III (4"-10")
- Register Compatibility:
  - Direct Read
  - ARB®V
  - ProRead AutoDetect
- Connection Wire:
  - Distances up to 1000 feet – AWG
  - #22 twisted pair cable



www.neptunetg.com

PS TRICONE 12.01  
© Copyright 2001, Neptune Technology Group Inc.  
ARB and TRICON are registered trademarks of Neptune Technology Group Inc.

### Distributed by:

Follin Flo-Controls  
39 Magnolia Ave. Cambridge, MA 02138  
Tel: (617) 290-2134 Web: www.FollinFlo-Controls.com  
Fax: (240) 250-8907